



Refrigerated containers

## RC40 Refrigeration/freezer container

Robust refrigeration/freezer container (40-ft reefer high cube) with a volume of 67 m<sup>3</sup>. The container features an aluminium T-profile floor, SST inner lining and double doors. The container can be moved with contents with a crane truck. The container does not meet the HACCP/GMP requirements.

### Technical specifications RC40

|                          |                   |                   |          |                       |                     |
|--------------------------|-------------------|-------------------|----------|-----------------------|---------------------|
| Amount of pallets (euro) | 23                | Current (nominal) | 17.6 A   | Height (internal)     | 2550 mm             |
| Volume                   | 67 m <sup>3</sup> | Recommended fuses | 25 A     | Door height           | 2500 mm             |
| Min. inside temperature  | -25 °C            | Phases            | 3 + PE   | Door width            | 2260 mm             |
| Max. inside temperature  | 25 °C             | Length (external) | 12190 mm | Treshold height, min. | 210 mm              |
| Min. outside temperature | -20 °C            | Width (external)  | 2440 mm  | Treshold height, max. | 270 mm              |
| Power connection         | 32 A CEE          | Height (external) | 2890 mm  | Max. load             | 1 Kg/m <sup>2</sup> |
| Voltage                  | 400 V             | Length (internal) | 11530 mm | Weight                | 4800 kg             |
| Current (max)            | 21 A              | Width (internal)  | 2280 mm  | Sound level (at 10 m) | 58 dB(A)            |