



## Freezer unit MV01

Ready-for-use mobile freezer unit with a volume of 84 m<sup>3</sup> and a large freezing overcapacity (temperature range down to minus 35 °C\*). The frozen storage cell has been fitted with a flat anti-skid floor, lighting, a door with frame heating that opens smoothly (also from the inside), and has a very low entry height. The frozen storage cell meets the HACCP/GMP requirements, and standard features include a data log system. Optional are wireless temperature control and monitoring. The unit is easy to install with a crane truck. This storage cell is low noise and low energy.



### Mértékadó jellegét meghatározza részére MV01



Flourescent lighting

Anti-skid floor

Door edge heating

Strip curtain



Data logger

Anti theft

### Opcionális kiegészítők MV01



Ride-in panel

Extention power cable

Plastic shelves

Extra power outlet

Light alarm / sound alarm

Elevation on brackets

Auxiliary vents

(De)moisturizing



Heating

Remote monitoring

### Műszaki elírások MV01

|                                      |                   |
|--------------------------------------|-------------------|
| Amount of pallets (euro)             | 26                |
| Volume                               | 84 m <sup>3</sup> |
| Min. inside temperature <sup>1</sup> | -35 °C            |
| Max. inside temperature              | 2 °C              |
| Power connection                     | 32 A CEE          |
| Voltage                              | 400 V             |
| Recommended fuses                    | 25 A              |
| Phases                               | 3 + N + A         |
| Length (external)                    | 12000 mm          |
| Width (external)                     | 3000 mm           |
| Height (external)                    | 3000 mm           |
| Door height                          | 2500 mm           |
| Door width                           | 1400 mm           |
| Threshold height                     | 200 mm            |
| Weight                               | 6200 kg           |
| Sound level (at 10 m)                | 50 dB(A)          |

<sup>1</sup> After approval of Coolworld International